

IN THE UNITED STATES  
PATENT AND TRADEMARK OFFICE

PATENT APPLICATION

Ananth Dodabalapur, Attila Mekis, John A. Rogers and Richart E. Slusher

CASE Dodabalapur 19-2-16-18

TITLE: ARTICLE COMPRISING A TWO-DIMENSIONAL PHOTONIC CRYSTAL  
COUPLER AND METHOD OF MAKING THE SAME

THE COMMISSIONER OF PATENTS AND TRADEMARKS  
WASHINGTON, D.C. 20231

SIR:

Enclosed are the following papers relating to the above-named application for patent:


Specification  
10 Informal sheets of drawings  
Declaration and Power of Attorney

CLAIMS AS FILED				
	NO. FILED	NO. EXTRA	RATE	CALCULATIONS
Total Claims	20 - 20 =		0 x \$18	\$0
Independent Claims	3 - 3 =	0	x \$78	\$0
Multiple Dependent Claim(s), if applicable			\$260	\$0
Basic Fee				\$760.
TOTAL FEE:				\$760.

Please file the application and charge Lucent Technologies Inc. Deposit Account No. 12-2325 the amount of \$760., to cover the filing fee. Duplicate copies of this letter are enclosed. In the event of non-payment or improper payment of a required fee, the Commissioner is authorized to charge or to credit Deposit Account No. 12-2325 as required to correct the error.

Please address all correspondence to **Anastasia P. Winslow, Esq., Mathews, Collins, Shepherd & Gould, P.A., 100 Thanet Circle, Suite 306, Princeton, NJ 08540.** Telephone calls should be made to Anastasia P. Winslow, Esq. at Area Code (609) 924-8555.

Respectfully,



Anastasia P. Winslow  
Reg. No. 40,875  
Attorney for Applicants

Date: January 11, 2000

MATHEWS, COLLINS, SHEPHERD & GOULD, P.A.  
100 Thanet Circle, Suite 306  
Princeton, NJ 08540  
Tel. (609) 924-8555  
Fax (609) 924-3036  
PT 13 8/92

jc675 U.S. PTO  
09/480409  
01/11/00

# ARTICLE COMPRISING A TWO-DIMENSIONAL PHOTONIC CRYSTAL COUPLER AND METHOD OF MAKING THE SAME

5 **Inventors: Ananth Dodabalapur, Attila Mekis, John A. Rogers, and Richart E. Slusher**

## **RELATED APPLICATIONS**

This application is a continuation-in-part of U.S. patent application Serial No. 09/385,167 filed August 30, 1999, which is incorporated herein by reference.

## 10 **FIELD OF THE INVENTION**

The present invention relates to a photonic crystal coupler and more particularly, to an article comprising a two-dimensional photonic crystal coupler which advantageously is integrated with one or more one-dimensional photonic crystal lasers.

## **BACKGROUND OF THE INVENTION**

15 Couplers are important devices for many communication applications and in integrated photonic circuits. Couplers are needed to combine or separate signals and to interconnect the various points of a communications network. There are many constraints involved with coupler design, however. Such constraints include the laser structure with which the coupler may be used, the number of ports, sensitivity to light transmission  
20 direction, wavelength selectivity, type of fiber, signal attenuation, and cost. High-power distributed feedback (DFB) lasers are light sources of choice in many optical communications systems, which makes coupling the laser light out of planar waveguides and possibly into fibers a crucial technological issue. Traditionally, one-dimensional

grating couplers (GCs) and focusing GCs have been used to couple laser light out of a waveguide plane and achieve coherent scattering of the light. See, e.g., A. Katzir *et al.*, APPL. PHYS. LETT. 30, 225 (1977); Loewen *et al.*, DIFFRACTION GRATINGS AND APPLICATIONS (M. Dekker, NY 1997); D. Heitmann *et al.*, APPL. PHYS. LETT. 37, 585  
5 (1980); Hatakoshi *et al.*, APPL. OPT. 23, 1749 (1984); P. Borsboom *et al.*, J. OPT. SOC. AM. A12, 1142 (1995).

There are drawbacks, however, with such one-dimensional gratings, particularly with regard to the directionality of the output light. The direction of the output light naturally affects how well the light may be coupled into receivers or other devices, e.g.,  
10 planar waveguides and fibers. Both one-dimensional grating couplers and focusing grating couplers have periodicity in a single spatial direction. One-dimensional GCs have straight grooves, whereas focusing GCs, also called grating lenses, have a curvilinear grating. The direction of light output from a coupler is determined by phase-matching the scattered wave to the guided wave. One-dimensional grating couplers couple light to a cylindrical  
15 wave, as shown in FIG. 1A, necessitating the use of additional optics to direct the light into a fiber. Focussing grating couplers focus light to a point in space in the vicinity of the grating at a distance on the order of the grating size, as shown in FIG. 1B. With focusing couplers, a receiver may only be placed at a certain fixed distance from the coupler, and in the far field, light is coupled to a spherical wave.

20 Additionally, semiconductor lasers using organic or polymeric materials and electrically-driven laser action have recently attracted a great deal of interest. Organic solid-state lasers have the potential to provide a compact low-cost laser source over a

broad range of wavelengths throughout the visible spectrum. Organic lasers also influence research in other areas and have led to advances with both organic and inorganic semiconductor lasers, as described in A. Dodabalapur *et al.*, “*Organic Solid-State Lasers: Past and Future*,” SCIENCE Vol. 277 (Sept. 19, 1997), at pp. 1787-1788, incorporated  
5 herein, and in U.S. patent application Serial No. 09/385,167, referenced above (hereinafter the “167 application”).

Examples of advances in organic or inorganic semiconductor lasers include the successful realization of distributed feedback (DFB) and distributed Bragg reflector (DBR) lasers with dye-doped polymers and the widespread use of InP-based DFB and  
10 DBR lasers. Such lasers exhibit superior single frequency operation and high-speed modulation characteristics, *e.g.*, as compared with Fabry-Perot lasers. DFB and DBR are deployed in many commercial systems including long-haul fiber optic communication systems. An assembly comprising a DBR or DBF laser monolithically integrated with an off-plane computer-generated waveguide hologram and semiconductor amplifier is  
15 disclosed in Feng *et al.*, “*Grating-Assisted Surface-Emitting Laser Transmitter with Image-Forming Capability*” IEEE Photonics Tech. Letters, Vol. 10, No. 12 (Dec. 1998). Feng *et al.* define their computer-generated hologram as “essentially a surface relief grating-like” structure the design of which is not clearly defined.

DFB and DBR lasers are examples of one-dimensional photonic-crystal lasers  
20 since they possess one-dimensional gratings as part of their structure. One-dimensional photonic crystal lasers provide many advantages. For example, the density of states is sharply peaked at the edges of the air and dielectric bands, leading to low thresholds.

Although two-dimensional photonic crystal lasers have been demonstrated {see, e.g., M. Meier *et al.*, APPL. PHYS. LETT. 86, 3502 (1999), which is incorporated herein}, for many applications one-dimensional lasers remain preferred.

As may be appreciated, those involved in the field of communications systems and semiconductor devices continue to seek to develop new designs to improve device efficiency and performance and to allow for the use of new materials, such as GaN and plastics. In particular, it would be advantageous to provide a coupler that avoids the directionality restraints of one-dimensional and focusing GCs that is compatible with one-dimensional photonic crystal lasers such as DFB and DBR lasers.

## **SUMMARY OF THE INVENTION**

Summarily described, the invention comprises an article that includes a two-dimensional photonic crystal coupler. The coupler comprises a core region disposed between two cladding regions, in which the core region has a grating formed in two-dimensions. Unlike traditional grating couplers, this two-dimensional photonic crystal coupler can couple light into a single or a discrete number of directions in the far-field. The coupler can be integrated with one-dimensional lasers, a distributed feedback laser, a distributed Bragg reflector laser, and integrated on the same waveguide as the lasers. The coupler can also be ensconced with other optical components (such as gratings) to form composite devices which effectively function as lasers with unique output coupling characteristics.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

To illustrate the invention, there is shown in the drawings a form of the invention which is presently preferred, it being understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown.

5        FIGS. 1A and 1B are schematic illustrations representing the directional output from one-dimensional grating and focusing couplers, respectively;

FIG. 2 is a schematic illustration representing the directional output from a two-dimensional grating coupler;

10        FIG. 3 is a schematic illustration reflecting the phase-matching condition in a reciprocal lattice of a triangular two-dimensional photonic crystal coupler;

FIGS. 4A and 4B are cut-away cross-sectional top and side views, respectively, of a waveguide structure comprising a two-dimensional photonic crystal coupler and laser;

15        FIG. 5 is a plot of the coupling constant and the ratio of the power coupled into air to the total scattered power, both as a function of grating depth, for the coupling structure of FIGS. 4A-4B;

FIG. 6A is a schematic cross-sectional side view of the waveguide laser-coupler device;

FIG. 6B is a schematic view taken along the cross-sectional line 6-6 of FIG. 6A;

20        FIG. 7 schematically illustrates a top view of a two-dimensional triangular lattice coupler integrated with six lasers;

FIG. 8A is a schematic illustration of a pattern for a photoresist layer for use in making the two-dimensional coupler ensconsed within a pair of DBR lasers;

FIG. 8B is a schematic illustration of a second pattern and dimensions for a photoresist layer for use in making the two-dimensional coupler ensconsed within a pair of DBR lasers; and

FIG. 9 is a schematic cross-sectional side view of a waveguide laser-coupler device together with a substrate and LED for use as a laser structure illustrating one exemplary application for the two-dimensional coupler.

## **DETAILED DESCRIPTION OF THE INVENTION**

With this invention, a two-dimensional photonic crystal grating coupler is provided that achieves dramatic advantages over traditional GCs in coupling directionality. Unlike traditional grating couplers, this two-dimensional photonic crystal coupler can couple light into a single or a discrete number of directions in the far-field; that is, the output light may be unidirectional or follow a plurality of discrete directions. Additionally, the inventive coupler can be integrated on the same waveguide as a one-dimensional laser, such as an organic DFB laser and fabricated together with the laser, thus realizing the advantages of both the one-dimensional laser and the two-dimensional coupler.

With the two-dimensional grating coupler, a core region is disposed between two cladding regions, in which the core region receives light from a first device and outputs light to a second device, i.e., the index of refraction of the core relative to the cladding is such that there is internal reflection of light at the core. The core region has a grating formed in two-dimensions. Introduction of periodicity in this additional spatial direction

increases the number of constraints on the output angles. Light is then coupled out into a single or a number of discrete directions, as schematically illustrated in FIG. 2. In other words, light is not output in a cylindrical or spherical wave, as with the one-dimensional GCs of the prior art (*e.g.*, as in FIGS. 1A-1B), but rather, it is unidirectional or follows a plurality of discrete paths. The two-dimensional coupler is a dramatic improvement over traditional grating couplers in coupling directionality.

The discussion below is divided into five parts. In part A, the coupling mechanism in two-dimensional photonic crystal couplers and the effect of design parameters on output directions are described. In Part B, numerical simulations are used to calculate coupling constants for a photonic crystal coupler in an exemplary waveguide structure. In Part C, examples are set forth for use of the photonic crystal coupler in conjunction with a one-dimensional laser and integration of the laser and coupler during fabrication. In Part D, an exemplary method of making the laser-coupler device is described. Then in Part E, contemplated applications for use of the two-dimensional photonic crystal coupler and the laser-coupler configuration are discussed.

#### *A. Coupling Mechanism and Effect of Design Parameters on Output Directions*

Factors applicable in designing a two-dimensional photonic crystal coupler may be analyzed by considering a grating in a planar dielectric waveguide on top of a substrate. Let the wavevector of the waveguided mode incident on the grating section be  $k$ , its free-space wavelength  $\lambda$ , the in-plane component of the scattered radiation wavevector  $K$ , and the polar angle of the output direction  $\theta$ . If the number of periods in the grating is large,



the field scattered by the grating will interfere constructively only in certain directions. The phase-matching condition is

$$k = K + G \quad (1)$$

where  $G$  is a reciprocal lattice vector by which the lattice diffracts the propagating mode out of the guide. The azimuthal angle of the radiation direction is easily determined from (1) and the polar angle from the same equation as

$$\sin \theta = \lambda |k - G| / 2\pi n \quad (2)$$

where  $n$  is the refractive index of the medium (air or substrate) into which the radiation is emitted.

The two-dimensional coupler may take many shapes and be fabricated with a variety of materials (as further described below); however, equations (1) and (2) above may be applied generally in designing the two-dimensional coupler and selecting the correct lattice parameters to achieve coupling in a desired direction. FIG. 3 illustrates the phase-matching condition in a reciprocal lattice of a triangular two-dimensional photonic crystal coupler for a guided mode wavevector. The emitted radiation is in two directions  $K, K'$  so this grating acts as a two-way splitter. Light is emitted into one half-space into two directions, with different azimuthal and polar angles. This is not possible with a traditional one-dimensional GC. Since  $\sin \theta \leq 1$ , there are only a finite number of reciprocal lattice vectors that satisfy Equation (2).

## B. Numerical Simulations For Calculating Coupling Constants For A Photonic Crystal Coupler In An Exemplary Waveguide Structure

The coupling constants for a photonic crystal coupler can be determined explicitly.

5 Consider for example a waveguide structure consisting of two layers disposed on a silicon substrate, partially illustrated in FIGS. 4A-4B, in which a two-dimensional coupler functions as both a laser and a coupler (thus, the laser is a two-dimensional laser). FIGS. 4A-4B showing the same cut-away sections of this exemplary waveguide structure, wherein FIG. 4A shows a top view (*i.e.*, of one lattice hole), and FIG. 4B shows a cross-sectional side view of the hole. The waveguide structure has a SiO<sub>2</sub> substrate 110 (with a refractive index  $n = 1.46$ ), and two overlying layers 111, 112, comprising a first layer 111 of 100 nm thick Si<sub>3</sub>N<sub>4</sub> (with a refractive index  $n = 2.0$ ) and a second layer 112 of an organic material (with a refractive index  $n = 1.7$ ). The lattice holes for forming the grating of the photonic crystal coupler are etched into the Si<sub>3</sub>N<sub>4</sub> layer before sublimation of the second layer 112 so that the organic material will fill the holes comprising the grating. 15 The photonic crystal is selected in this example to be a square lattice of holes with lattice constant  $a$ , hole radius  $r = 0.375a$ , and hole depth  $b$ . However, vertical coupling can also be achieved using other kinds of lattices, such as triangular, rectangular, honeycomb, etc.

In this example, the lattice parameters are chosen as follows. To satisfy Equation 20 (2) for vertical emission ( $\theta = 0$ ),  $k$  must be a reciprocal lattice vector. For only vertical emission into both substrate and air, the right-hand-side must be larger than 1 for  $|k - G| > 0$ . This is possible when  $a < \lambda/n$ . In terms of the guide effective index  $n_e$ ,  $ka/2\pi < n_e/n$  must hold for both substrate and air refractive indices  $n$ . In this example,  $\lambda = 650$  nm,  $n_e = 1.63$  and  $n = 1.46$ ; consequently,  $k = 2\pi/a$ . This yields a lattice constant  $a = 400$

nm, which is achievable with lithographical methods. If the index contrast between the guide and the substrate is larger than set forth in this example and the ratio  $n_e/n$  is greater, several feasible lattice constants could be selected.

The next step is to calculate the coupling constant for the waveguide grating. For simplicity, let the guided mode propagation direction be  $x$ , and let the grating have length  $L_x$  in this direction. As the mode propagates, its intensity decays exponentially due to scattering losses. The amplitude coupling constant  $\alpha$  is defined as one half of the fractional change in the power flux  $P$  along the guide. The power flux and the energy  $E$  per unit length are related to the group velocity  $v_g$  of the waveguide without the grating through

$$P = v_g E / L_x \quad (3)$$

and the total radiated power scattered by the grating is  $P_s = dE/dt$ . Therefore we can express  $\alpha$  in terms of  $E$  as

$$\alpha = -\frac{1}{2P} \frac{dP}{dx} = -\frac{1}{2P} \frac{P_s}{L_x} = \frac{1}{2v_g} \frac{d(\ln E)}{dt} \quad (4)$$

In these numerical simulations, Maxwell's equations may be solved using a finite-difference scheme on a three-dimensional rectangular grid. See, e.g., K.S. Kunz *et al.*, THE FINITE DIFFERENCE TIME DOMAIN METHOD FOR ELECTROMAGNETICS (CRC press, Boca Raton 1993). The grid is periodic in the  $x$ - and  $y$ - directions and contains one unit cell of the photonic crystal slab. In the  $z$ - direction, the cell is terminated by a second-order Mur's absorbing boundary condition. A TE polarized dipole source with a Gaussian

time-profile placed in the center of the slab excites a guided mode of the slab. The energy in the cell and the flux through the top and bottom are measured as a function of time. The cell is long enough in the  $z$ - direction so that the escaping flux due to the finite extent of the cell is negligible compared to the energy in the mode for a slab without the grating.

5 The excited mode is a superposition of two counter-propagating waves. The grating has a plane of symmetry perpendicular to the propagation direction  $x$ . The two propagating modes combine to give a mode that is symmetric and one that is asymmetric with respect to reflection through this plane. The asymmetric mode cannot couple to free-space plane waves, so no energy is lost from the slab when this mode is excited. The  
10 symmetric mode, however, loses energy at twice the rate of the propagating mode. In contrast to one-dimensional gratings, modes can combine in a more complicated fashion; for instance, four modes, or even six, can mix in a triangular lattice.

We observe an exponential decay of the energy of the symmetric mode excited by the pulse, as expected. We use equation (4) to determine  $2\alpha$  from the decay constant.

15 The unperturbed waveguide for which  $v_g$  is used in (4) is not simply the original waveguide with  $b = 0$  but is defined by the zeroth order component in the Fourier decomposition of the dielectric constant. For fixed  $b$ , this is a waveguide with  $b = 0$  and effective organic thickness  $h = h_e = 50nm + \pi r^2 b$  and  $d = 150nm - h$ . The resulting group velocity found from the dispersion relation for this waveguide fits very well in the  
20 formula  $v_g / c = 0.508 + (b + 0.125)^2$ , where  $b$  is given in units of  $\mu m$ .

FIG. 5 is a plot of the resulting coupling constant and the ratio of the power coupled into air to the total scattered power, both as a function of the grating depth. The

dashed line reflects power coupled into air divided by the total power coupled out of the guide, and the solid line reflects  $\alpha$ . For small  $b$ , the increase is quadratic. At its maximum, the coupling constant exceeds  $110 \text{ cm}^{-1}$ . Even though this coupling constant would still require a grating of length  $\approx 100 \mu\text{m}$ , the coupler size can be reduced by

5    ensconcing the photonic crystal coupler within one-dimensional gratings at each end to realize a resonant-cavity coupler. The beam divergence of the emitted light beam is on the order of  $\lambda/nL$ , where  $L$  is the size of the grating in the direction in which the beam divergence is measured. For a  $30 \mu\text{m} \times 30 \mu\text{m}$  grating this is about  $1^\circ$  for radiation into air, thus enabling compact and very efficient photonic crystal couplers. The size of the  
10    couplers may be reduced even further allowing for facile and efficient coupling into single-mode fibers.

The coupling efficiency as shown in FIG. 5 increases with  $b$  and exceeds 60% at the maximum depth considered. Since at  $b = 0$  the ratio is undetermined, the efficiency for small  $b$  was obtained from interpolation using a structure with  $b < 0$ , that is, a  $\text{Si}_3\text{N}_4$   
15    cylinder of height  $-b$  protruding into the organic layer. The increase with  $b$  and the turnoff at large grating depth can be understood by considering the scattering due to the perturbation as a source of a plane wave in the  $\text{Si}_3\text{N}_4$  layer. The coefficient of transmission into air through an organic layer of effective thickness  $h_e$ , and index  $n$  has maxima at  $h_e = N\pi c/2\omega n$ ,  $N$  being an odd integer. From this picture we expect  
20    transmission to be approximately sinusoidal as  $h_e$  changes, with a maximum at  $h_e = 96 \text{ nm}$ , or  $b = 103 \text{ nm}$  (from  $N = 0$ ). This is in good qualitative agreement with the calculated coupling efficiency.

As can be seen, two-dimensional photonic crystal couplers can couple light into a discrete number of directions in the far-field. The two-dimensional photonic crystal couplers can effect unidirectional coupling and compact photonic crystal couplers with short coupling lengths ( $< 30\mu\text{m}$ ) and small beam divergences ( $< 5$  degrees) can be realized and fabricated together with planar DFB lasers. Because of the time-reversibility of Maxwell's equations, light can be coupled into planar waveguides with the same type of photonic crystal couplers from vertically emitting sources, such as vertical cavity surface emitting lasers.

### C. Exemplary Photonic Crystal Coupler and One-Dimensional Laser Structures

A single one-dimensional photonic crystal laser (e.g., DBR laser), may be integrated with the two-dimensional coupler. For example, FIG. 6 is a schematic cross-sectional side view of the coupler integrated with a laser. The waveguide laser 30 has a core region 32 comprised of a material having a first index of refraction surrounded by cladding layers 34a, 34b having a second index of refraction lower than the first so that light pumped into the core region 32 will be guided therein (e.g., along the guided mode 35), by total internal reflection. Within the core region 32 of the laser is fabricated a one-dimensional grating 36. The laser 30 is joined with coupler 40, having core region 42, cladding regions 44a, 44b, and a two-dimensional grating 46 formed in the core.

The laser 30 and coupler 40 share a common waveguide and can be formed on the same substrate. When the laser has a high absorption coefficient (in the unpumped state), it may be advantageous to use a slightly different material composition in the coupler to reduce absorption losses, as the coupler is not pumped. For example, the coupler may

have a loss coefficient smaller than the coupling constant. A design guideline is that the loss coefficient of the coupler is  $< 10 \text{ cm}^{-1}$ . FIG. 6B shows a schematic cross-sectional top view of the coupler 40 of FIG. 6A, along the cross-sectional line 6-6 of FIG. 6A, showing preferred parameters for coupling. In particular, as shown in FIG. 6B, for a square lattice the distance spanning the side of each square of the lattice is  $0.22 \text{ } \mu\text{m}$  and the distance from one corner of one square to the proximal corner of the next adjacent square is  $0.44 \text{ } \mu\text{m}$ .

Additionally, a plurality of one-dimensional photonic crystal lasers may be integrated with the same coupler. In this case, the coupler functions as a mixer as well as a coupler. The number of lasers and orientation relative to the coupler should be selected so that the two-dimensional character of the coupler is retained. For example, when a coupler having a two-dimensional triangular lattice is used, six lasers may be combined at directions that are 60 degrees apart relative to each other. Such an arrangement is schematically shown in FIG. 7A, in which each arrow represents the path of light emitted from a laser that is integrated with the coupler. In this embodiment, all six modes can mix. The parameters of the two-dimensional lattice will affect the number of points in real space that the laser emissions are coupled to. For example, when a two-dimensional lattice with square symmetry is used, mixing and combining of the modes can occur along four directions. With the two-dimensional triangular lattice, six directions may be used, and also, the emissions from all six lasers can be directed vertically, which is advantageous for high-powered lasers.

05430409-011400  
00779-60403450

The two-dimensional photonic crystal coupler also may be ensconced within the one-dimensional laser structure. In other words, the coupler can be fabricated as a “defect” in a one-dimensional photonic crystal laser, and the gratings of the one-dimensional photonic crystal laser function as mirrors which create a “resonant cavity coupler.” For example, FIG. 7B shows the index modulation pattern of the composite device where the two-dimensional photonic crystal coupler is ensconced between two DBR mirrors. In this case, the two-dimensional coupler is formed with a square lattice. The width of the waveguide (which runs substantially perpendicular to the Bragg mirrors) can be reduced to dimensions that are sufficiently small to function in single mode. The dimension of the waveguide will depend on the wavelength and materials. For example, at a wavelength of 700 nm, a III-IV semiconductor laser can function as a single-mode laser when the width of the waveguide is about 2-3 microns, wherein the “width” denotes the dimension perpendicular to the direction of light propagation and parallel to the plane of the layers (core, cladding, etc.) (*e.g.*, illustrated in FIG. 6A with reference “w”).

The length of the coupler advantageously is approximately the same as the width of the waveguide. The coupling constant of the two-dimensional photonic crystal may be small (*e.g.*, about  $100\text{ cm}^{-1}$ ) such that over a coupler length of 2-3 microns, a small fraction (*e.g.*, about 2 percent) of the guided light can be outcoupled. However, the resonant structure will enhance the amount of coupling.

#### D. *Method of Making the Laser-Coupler Device*

By way of example, a two-dimensional coupler can be ensconced within two DBR lasers for use as a dielectric waveguide as follows. A silicon substrate is provided and



coated with a thick layer (e.g., about 4 micrometers in thickness) of SiO<sub>2</sub> having a refractive index of about 1.5. A photoresist is applied to the Si/SiO<sub>2</sub> structure and patterned as shown in FIG. 8A. The exposed portions of the sample (*i.e.*, not covered by the photoresist) are then etched, applying methods known in the field for etching photoresist. For example, the sample may be etched by a plasma with CHF<sub>3</sub> for about 2 minutes at a pressure of about 30 mTorr and a plasma voltage of about 300 V which typically etches to a depth of about 30 nm in the SiO<sub>2</sub> layer. The photoresist is then removed, applying methods known in the field, *e.g.*, by use of an oxygen plasma. A pattern is thus formed on the sample that is inverse of the pattern shown in FIG. 8A, to produce first order grating regions 50, and second order (square lattice) grating region 60. The photoresist preferably is applied and the sample etched to produce a periodicity of 210 nm for the first order grating and 420 nm for the second order grating. Of course, other patterns may be used to form gratings with different structures. In integrating a two-dimensional coupler with a one-dimensional laser, basically a two-dimensional latticed pattern is formed adjacent at least one one-dimensional linear pattern.

The sample is again coated with thick photoresist and patterned to form a cross-shaped pattern as illustrated in FIG. 8B. As shown in FIG. 8B, each of the arms of the cross are substantially equally-sized and about 2 or 3  $\mu\text{m}$  thick ( $t = 2\text{-}3\mu\text{m}$ ) and about 25  $\mu\text{m}$  long ( $l = 25\text{ m}$ ). The sample is then etched to a depth of about 3 micrometers, with the photoresist protecting the grating patterns previously defined. The photoresist is then removed, applying known methods, to expose the one- and two-dimensional grating regions.

A thin film (*e.g.*, ~ 200 nm) of 8 hydroxyquinoline aluminum (Alq) doped with 1% by weight of DCM (a laser dye available from Exciton Inc.) is deposited above the structure. The optical properties of Alq doped with DCM and its use as a laser gain medium are described in the literature, and suitable compositions and mixtures for use as the gain medium are further described in A. Dodabalapur, *"Resonators and Materials for Organic Lasers Based on Energy Transfer,"* IEEE J. OF SELECTED TOPICS IN QUAN. ELEC., Vol. 4, No. 1 (Jan./Feb. 1998), which is incorporated herein by reference. Alq doped with DCM has a refractive index of about 1.65-1.85. The thickness of the organic film is selected so that the organic layer will function as the core, whereas the SiO<sub>2</sub> layer and air will serve as the cladding. The thin gain medium and the depth of the etched waveguide are such that the optical mode or modes that are guided are isolated from the substrate. A suitable waveguide depth is, for example, 3 μm. The term "cross-coupled" laser may also be used to designate this device. Here, the coupler part cross-couples the laser radiation created in the arms.

The resulting structure may be pumped with a nitrogen laser (having a wavelength of 337 nm). The Alq molecules will absorb this light, and the excitations that are created are transferred to the DCM molecules by Forster transfer. If the excitation intensity is sufficiently high, laser action is created, and the waveguide emission is coupled out of the plane by the two-dimensional square lattice. With a coupler fabricated with the parameters of this example, the laser emission will be at about 640 nm and the light will be output coupled at an angle of approximately 90 degrees relative to the surface plane of the substrate. The geometry described with reference to FIGS. 8A and 8B can also be advantageously employed for the case of the resonant cavity coupler described previously.

Cross-coupled lasers can also be implemented with other types of 2D photonic crystals besides the square lattice described above. For example, a triangular lattice coupled be used for the central coupler portion. In this case, three lasers could be used intersecting at an angle of 120 degrees with respect to each other. In cross-coupled lasers, some of the arms can be passive, *e.g.*, with no optical gain generated in those portions. Additionally, in certain cross-coupled lasers, the different arms may be injection locked to obtain single mode operation. The phenomenon of injection locking is well known in the art.

#### *E. Applications*

This inventive laser-coupler configuration may be used in conjunction with a laser structure for achieving electrically-driven lasing, invoking properties of both organic and polymeric LEDs and photoexcited lasers, as described in the '167 application. FIG. 9 shows a schematic cross-sectional side view of a structure for a laser including a waveguide laser-coupler. In FIG. 9, the laser structure includes a substrate 10 having a first side 11 and a second side 12. An LED 20 is fabricated on the first side 11, and a waveguide laser 30 is fabricated on the second side 12. The laser 30 is combined with an output coupler 40 to direct the laser emission in a desired direction. The substrate may be fabricated with glass or plastic and is transparent to visible light. A dielectric quarter wave stack layer 15 may be disposed between the substrate 10 and LED 20. The LED 20 may comprise a planar microcavity LED, as described in A. Dodabalapur *et al.*, "*Physics and Applications of Organic Microcavity Light Emitting Diodes*," J. APPL. PHYS. Vol. 80 (12)

(Dec. 15, 1996), at pp. 6954-6964, incorporated herein. The substrate may be configured as described in the '167 application.

The above laser structure represents just one of the many possible applications for the two-dimensional photonic crystal coupler. The coupler may be used with various other lasers and communications devices. For example, with the inventive coupler, light may be received from vertically-emitting sources, such as vertical cavity surface emitting lasers, and coupled into planar waveguides. The couplers may be implemented with lasers based on InP substrates emitting at 1.3 to 1.6  $\mu\text{m}$  useful in optical communications systems, and surface emitting lasers may be used. The couplers or device structures shown in FIGS. 8A and 8B also may be implemented with lasers based on GaN, InGaN and AlGaIn, contemplated for use as short wavelength sources (*e.g.*, about  $< 500 \text{ nm}$ ), useful for many applications including information storage and CDROMs. Again, a surface emitting laser technology can be used. Optically-pumped lasers based on rare-earth doped dielectrics (*e.g.*, erbium doped  $\text{SiO}_2$ ) can be used with the two-dimensional couplers, for applications in optical amplifiers and lasers. The invention also can be integrated with quantum cascade lasers useful for mid-infrared wavelengths, and a surface emitting quantum cascade laser can be achieved.

It should be understood that the above-described applications are exemplary only, and that the present invention may be embodied in other specific forms without departing from the spirit or essential attributes therefor. Accordingly, reference should be made to appended claims, rather than to the foregoing specification, as indicating the scope of the invention.

## **CLAIMS:**

The invention claimed is:

1. An article including a coupler comprising a core region disposed between two cladding regions, in which the core region receives light from at least one first device and  
5 outputs light to at least one second device, the core region having a grating formed in two-dimensions so that light is output from the coupler in at least one discrete direction.

2. The article of claim 1 in which the at least one first device is selected from a distributed feedback laser and a distributed Bragg reflector laser.

3. The article of claim 2 in which the coupler is integrated on the same waveguide as  
10 the at least one first device.

4. The article of claim 1 in which one of the two cladding regions comprises air.

5. The article of claim 1 in which one of the two cladding regions comprises SiO<sub>2</sub>.

6. The article of claim 1 in which the core region comprises an organic material.

7. The article of claim 6 in which the core region comprises 8-hydroxyquinoline aluminum doped with a laser dye.

8. The article of claim 1 in which the two-dimensional grating comprises a square or  
5 a triangular latticed grating.

9. The article of claim 8 comprising the coupler ensconced within at least two distributed Bragg reflector mirrors.

10 10. The article of claim 1 in which the at least one first device comprises a plurality of lasers.

11. The article of claim 10 in which the coupler is integrated on the same substrate as the plurality of lasers for emitting light to the coupler along a plurality of directions.

15

12. The article of claim 1 in which the coupler is ensconced between two distributed Bragg reflector lasers.

13. The article of claim 1 in which the coupler is a two-dimensional photonic crystal ensconced between a plurality of one-dimensional photonic crystal layers functioning as mirrors to define a resonant cavity coupler.

5 14. The article of claim 1 in which the first device comprises a vertical cavity surface emitting laser.

15. The article of claim 1 in which the second device comprises a planar waveguide.

10 16. The article of claim 1 in which the at least one first device is selected from lasers fabricated with InP, GaN, InGaN, AlGaN, InGaAs, InGaAsP, GaAs, and AlGaAs.

17. The article of claim 1 in which the first device comprises a quantum cascade laser.

15 18. An optical communications system comprising the article of claim 1.

19. An article comprising a two-dimensional photonic crystal coupler integrated with at least one one-dimensional photonic crystal laser wherein the gratings of the one-dimensional photonic crystal laser function as mirrors to define a resonant cavity coupler.

20. A method of making a two-dimensional photonic crystal coupler integrated with a one-dimensional laser comprising

coating a silicon substrate with a layer of  $\text{SiO}_2$ ;

applying a first layer of photoresist on the  $\text{SiO}_2$  layer;

5 patterning the first layer of photoresist to define a two-dimensional latticed pattern adjacent at least one one-dimensional linear pattern;

etching the exposed areas of the structure not covered by the first layer of photoresist to define a two-dimensional grating region adjacent a one-dimensional grating region;

10 removing the first layer of photoresist;

covering the one and two-dimensional grating regions with a second layer of photoresist to define second exposed areas of the structure beyond the grating regions;

etching the second exposed areas of the structure;

removing the second layer of photoresist; and

15 applying a layer of organic material over the structure.



## ABSTRACT

A two-dimensional photonic crystal coupler is disclosed, together with a cross-coupled laser structure that is based on a two-dimensional photonic crystal coupler stage. Unlike traditional grating couplers, this two-dimensional photonic crystal coupler can  
5 couple light into a single or a plurality of discrete directions in the far-field, *i.e.*, the output light may be unidirectional or discrete. The coupler can be integrated with one-dimensional lasers, a distributed feedback laser, a distributed Bragg reflector laser, and integrated on the same waveguide as the lasers. A resonant cavity coupler design improves the coupling efficiency of two-dimensional photonic crystal-based couplers.

Prior ART




FIG. 2





FIG 3



a

FIG. 4A




FIG. 4B




Fig. 5

007772" 60703460




Fig. 6A

09420409-01400




Fig- 6B

00770-60409460






Fig. 7



FIG. 8A








Fig. 9

IN THE UNITED STATES  
PATENT AND TRADEMARK OFFICE

Declaration and Power of Attorney

As the below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled **ARTICLE COMPRISING A TWO-DIMENSIONAL PHOTONIC CRYSTAL COUPLER AND METHOD OF MAKING THE SAME** the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by an amendment, if any, specifically referred to in this oath or declaration.

I acknowledge the duty to disclose all information known to me which is material to patentability as defined in Title 37, Code of Federal Regulations, 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

None

I hereby claim the benefit under Title 35, United States Code, 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

None

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

00779 6040946

I hereby appoint the following attorney(s) with full power of substitution and revocation, to prosecute said application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith:

Lester H. Birnbaum	(Reg. No. 25830)
Richard J. Botos	(Reg. No. 32016)
Jeffery J. Brosemer	(Reg. No. 36096)
Kenneth M. Brown	(Reg. No. 37590)
Craig J. Cox	(Reg. No. 39643)
Donald P. Dinella	(Reg. No. 39961)
Guy Eriksen	(Reg. No. 41736)
Martin I. Finston	(Reg. No. 31613)
James H. Fox	(Reg. No. 29379)
William S. Francos	(Reg. No. 38456)
Barry H. Freedman	(Reg. No. 26166)
Julio A. Garceran	(Reg. No. 37138)
Mony R. Ghose	(Reg. No. 38159)
Jimmy Goo	(Reg. No. 36528)
Anthony Grillo	(Reg. No. 36535)
Stephen M. Gurey	(Reg. No. 27336)
John M. Harman	(Reg. No. 38173)
Michael B. Johannesen	(Reg. No. 35557)
Mark A. Kurisko	(Reg. No. 38944)
Irena Lager	(Reg. No. 39260)
Christopher N. Malvone	(Reg. No. 34866)
Scott W. McLellan	(Reg. No. 30776)
Martin G. Meder	(Reg. No. 34674)
John C. Moran	(Reg. No. 30782)
Michael A. Morra	(Reg. No. 28975)
Gregory J. Murgia	(Reg. No. 41209)
Claude R. Narcisse	(Reg. No. 38979)
Joseph J. Opalach	(Reg. No. 36229)
Neil R. Ormos	(Reg. No. 35309)
Eugen E. Pacher	(Reg. No. 29964)
Jack R. Penrod	(Reg. No. 31864)
Daniel J. Piotrowski	(Reg. No. 42079)
Gregory C. Ranieri	(Reg. No. 29695)
Scott J. Rittman	(Reg. No. 39010)
Eugene J. Rosenthal	(Reg. No. 36658)
Bruce S. Schneider	(Reg. No. 27949)
Ronald D. Slusky	(Reg. No. 26585)
David L. Smith	(Reg. No. 30592)
Patricia A. Verlangieri	(Reg. No. 42201)
John P. Veschi	(Reg. No. 39058)
David Volejnicek	(Reg. No. 29355)
Charles L. Warren	(Reg. No. 27407)
Jeffrey M. Weinick	(Reg. No. 36304)

027773 53469460

(Reg. No. 17765)

Post Office Address: 540 Memorial Drive, Apt. 1409  
Cambridge, Massachusetts 02139

Inventor's  
signature \_\_\_\_\_ Date \_\_\_\_\_

Citizenship: United States of America

Post Office Address: 1200 Springfield Avenue, Apt. 1C  
New Providence, New Jersey 07974

Full name of 4th joint inventor: RICHART ELLIOTT SLUSHER

Inventor's  
signature \_\_\_\_\_ Date \_\_\_\_\_

Residence: Lebanon, County of Hunterdon and State of New Jersey

Citizenship: United States of America

Post Office Address: 79 Guinea Hollow Road  
Lebanon, New Jersey 08833

[illegible]

**ATTACHMENT A**

Attorney Name(s):	Bruce M. Collins	Reg. No.:	20,066
	Ronald Gould	Reg. No.:	28,299
	Diane Dunn McKay	Reg. No.:	34,586
	Glen E. Books	Reg. No.	24,950
	Anastasia P. Winslow	Reg. No.:	40,875
	Charles J. Brumlik	Reg. No.:	42,367
	Mary S. Kakefuda	Reg. No.	39,245

Telephone calls should be made to Anastasia P. Winslow at:

Phone No.: 609-924-8555

Fax No.: 609-924-3036

All written communications are to be addressed to:

Anastasia P. Winslow, Esq.  
Mathews, Collins, Shepherd & Gould, P.A.  
100 Thanet Circle, Suite 306  
Princeton, NJ 08540

609-924-8555